

AQUENCE



Aquence GL

High-performance casein-based adhesive range for glass labeling.

- » 100% zinc and borax free labeling adhesives
- » High processing and w quality
- » Widest field of applications
- » Efficient consumption
- » Excellent machinability
- » Sustainable adhesive solution





Aquence GL

High-performance adhesive range for glass labeling.

	Aquence GL 725 Eticol	Aquence GL 700 Plus Eticol	Aquence GL 701 Plus Eticol	Aquence GL 702 N Eticol
Application:	Versatile use, multipurpose product, high-performance, good IWR, foiling	High tack product, good flow properties combined with excellent machinability	Versatile use, foiling, efficient consumption on cold/wet bottles, fast setting	Highest tack level, high-performance, highest CWR, economic consumption, problem solver
Viscosity: Brookfield at 23°C	80 000 mPas	70 000 mPas	85 000 mPas	65 000 mPas
Wet tack:	medium	high	medium	very high
Setting time:	medium	fast	very fast	fast
Recommended application temperature:	24 - 28°C	15 - 30°C	24 - 28°C	24 - 28°C

Try Aquence GL now!

To experience how our Aquence GL range can improve your bottle labeling operation, please contact your local sales representative for more information and assistance with product trials.

Scan vCard:



Henkel AG & Co. KGaA
40191 Düsseldorf, Germany
Phone: +49 211 797-3654
Fax: +49 211 798-2312
Email: labeling@henkel.com
www.henkel.com

